
ideal lux. | Smile



| Code | 189604 |
|------------------|------------------------------|
| Item name | SMILE 15W CRI90 24° 3000K BK |
| Source | LED COB PHILIPS |
| Power | 15W |
| Driver included | RX-POWER |
| Driver available | No |
| Lumen | 1200 Lm |
| MacAdam | SDCM 4 |
| Beam | 24° |
| CCT | 3000K |
| CRI | ≥92 |
| UGR | - |
| LED Life | 50.000 h |
| Insulation class | Class II |
| IP | 20 |
| Material | Aluminum |
| Warranty | 5 years |
| Net Weight | 0,610 Kg |
| Volume | 0,0046 m³ |



90° 350°

 \bigcirc

18 cm

12,2 cm

TRACKLIGHTS

Cylindrical aluminum projector (extrusion + CNC manufacturing + forging) suitable for installation on three-phase track. White or black powder coating, 350 ° rotating head and 90 ° adjustable, the power driver is included and is located in the cylindrical body of the projector itself; light source with integrated LED COB technology, available with a color temperature of 3000K or 4000K and with color rendering index up to 90; starting binning ≤ 4-Step MacAdam; min. 80% of luminous flux remaining after 50000 h duration; symmetrical beam optic with three different emission angles and glare control (UGR <19); assembly and disassembly without tools; IP 20 protection; insulation class II. Ideal for the installation in big rooms, where great flexibility and color rendering is required, such as MUSEUM, COMMERCIAL and RETAIL









ideal lux. | Smile



Code Item name 189536 SMILE HONEYCOMB PER TRACKLIGHTS 15W

Code Item name

Code Item name 189543 SMILE DIFFUSORE ELLITTICO PER TRACKLIGHTS 15W

189505 SMILE ANELLO FRONTALE BIANCO PER TRACKLIGHTS 15W

Code Item name

170152 LINK SINGLE CONNECTION BK ON-OFF

