ideal lux. | Smile



Code 189628

Item name SMILE 15W CRI80 24° 4000K BK

Source LED COB PHILIPS

Power 15W

Driver included **RX-POWER**

Driver available


Lumen 1700 Lm MacAdam SDCM 4 Beam

CCT 4000K CRI ≥82 UGR

LED Life 50.000 h Insulation class Class II 20

Material Aluminum Warranty 5 years Net Weight 0,610 Kg Volume 0,0046 m³







located in the cylindrical body of the projector itself; light source with integrated LED COB technology, available with a color temperature of 3000K or 4000K and with color

TRACKLIGHTS

rendering index up to 90; starting binning ≤ 4-Step MacAdam; min. 80% of luminous flux remaining after 50000 h duration; symmetrical beam optic with three different emission angles and glare control (UGR <19); assembly and disassembly without tools; IP 20 protection; insulation class II. Ideal for the installation in big rooms, where great flexibility and color rendering is required, such as MUSEUM, COMMERCIAL and RETAIL

Cylindrical aluminum projector (extrusion + CNC manufacturing + forging) suitable for installation on three-phase track. White or black powder coating, 350 ° rotating head and 90° adjustable, the power driver is included and is










ideallux. | Smile

Code 189536

Item name

SMILE HONEYCOMB PER TRACKLIGHTS 15W



Code 189543

Item name SMILE DIFFUSORE ELLITTICO PER TRACKLIGHTS 15W



Code 189505

Item name SMILE ANELLO FRONTALE BIANCO PER TRACKLIGHTS 15W



Code 170152

Item name LINK SINGLE CONNECTION BK ON-OFF

