## ideal lux. | Smile



Code 189789

Item name SMILE 15W CRI90 36° 3000K BK

Source LED COB PHILIPS

Power 15W

Driver included RX-POWER

Driver available No


Lumen 1200 Lm MacAdam SDCM 4

Beam 36°
CCT 3000K
CRI ≥92
UGR -

LED Life 50.000 h
Insulation class Class II
IP 20

Material Aluminum
Warranty 5 years
Net Weight 0,610 Kg
Volume 0,0046 m³







## TRACKLIGHTS

Cylindrical aluminum projector (extrusion + CNC manufacturing + forging) suitable for installation on three-phase track. White or black powder coating, 350 ° rotating head and 90° adjustable, the power driver is included and is located in the cylindrical body of the projector itself; light source with integrated LED COB technology, available with a color temperature of 3000K or 4000K and with color rendering index up to 90; starting binning ≤ 4-Step MacAdam; min. 80% of luminous flux remaining after 50000 h duration; symmetrical beam optic with three different emission angles and glare control (UGR <19); assembly and disassembly without tools; IP 20 protection; insulation class II. Ideal for the installation in big rooms, where great flexibility and color rendering is required, such as MUSEUM, COMMERCIAL and RETAIL










## ideallux. | Smile

Code 189536

Item name

SMILE HONEYCOMB PER TRACKLIGHTS 15W



Code 189543

Item name SMILE DIFFUSORE ELLITTICO PER TRACKLIGHTS 15W



Code 189505

Item name SMILE ANELLO FRONTALE BIANCO PER TRACKLIGHTS 15W



Code 170152

Item name LINK SINGLE CONNECTION BK ON-OFF

