


ideal lux | Basic Accent

DOWNLIGHT


Die-cast aluminum recessed spotlight with round seal. Suitable for the installation on plasterboard ceiling. Matt white finish; COB Chip on Board and SMD technology; available in different color temperatures 3000k and 4000k and with three different optics; CRI \geq 80; protection IP20; insulation class II.



Code	193373
Item name	BASIC ACCENT 20W 4000K
Source	LED COB PHILIPS
Power	20W
Driver included	PHILIPS ON-OFF
Driver available	1-10V / DALI
Lumen	2100 Lm
MacAdam	SCDM 4
Beam	55°
CCT	4000K
CRI	\geq 80
UGR	<19
LED Life	30.000 h
Insulation class	Class II
IP	44
Material	Aluminum
Warranty	5 years
Net Weight	0,660 Kg
Volume	0,0027 m ³
Base / Hole	\varnothing 12,5 cm



14,4 cm



7,1 cm



Code	218847
Item name	BASIC DRIVER 1-10V 20W
Power	20W
Output	9/28Vdc
Current	700 mA
Measure	150 x 43 x 29 mm



Code	220789
Item name	BASIC DRIVER DALI 20W
Power	25W
Output	20/23Vdc
Current	700 mA
Measure	130 x 43 x 30 mm