


# ideal lux | Basic Wide

## DOWNLIGHT

Die-cast aluminum recessed spotlight with round seal. Suitable for the installation on plasterboard ceiling. Matt white finish; COB Chip on Board and SMD technology; available in different color temperatures 3000k and 4000k and with three different optics; CRI  $\geq 80$ ; protection IP20; insulation class II.



Code	193427
Item name	BASIC WIDE 20W 4000K
Source	LED COB SAMSUNG
Power	20W
Driver included	PHILIPS
Driver available	1-10V   DALI
Lumen	2100 Lm
MacAdam	4SDC
Beam	87°
CCT	4000K
CRI	$\geq 80$
UGR	<21
LED Life	30.000 h
Insulation class	Class II
IP	44
Material	Aluminum
Warranty	5 years
Net Weight	0,630 Kg
Volume	0,0027 m <sup>3</sup>
Base / Hole	$\varnothing 12,5$ cm





Code	218847
Item name	BASIC DRIVER 1-10V 20W
Power	20W
Output	9/28Vdc
Current	700 mA
Measure	150 x 43 x 29 mm



Code	220789
Item name	BASIC DRIVER DALI 20W
Power	24W
Output	20/23Vdc
Current	1050 mA
Measure	130 x 43 x 30 mm