

# ideal lux | Basic Accent




## DOWNLIGHT

Die-cast aluminum recessed spotlight with round seal. Suitable for the installation on plasterboard ceiling. Matt white finish; COB Chip on Board and SMD technology; available in different color temperatures 3000k and 4000k and with three different optics; CRI  $\geq 80$ ; protection IP20; insulation class II.



Code	193465
Item name	BASIC ACCENT 15W 3000K
Source	LED COB PHILIPS
Power	15W
Driver included	PHILIPS
Driver available	1-10V   DALI
Lumen	1450 Lm
MacAdam	4SDC
Beam	55°
CCT	3000K
CRI	$\geq 80$
UGR	<18
LED Life	30.000 h
Insulation class	Class II
IP	44
Material	Aluminum
Warranty	5 years
Net Weight	0,660 Kg
Volume	0,0027 m <sup>3</sup>
Base / Hole	$\varnothing$ 12,5 cm





Code	218830
Item name	BASIC DRIVER 1-10V 15W
Power	15W
Output	9/33Vdc
Current	450 mA
Measure	150 x 43 x 29 mm



Code	220796
Item name	BASIC DRIVER DALI 15W
Power	17W
Output	15/24Vdc
Current	700 mA
Measure	130 x 43 x 30 mm