


ideal lux | Basic Wide



Code	193526
Item name	BASIC WIDE 15W 3000K
Source	LED COB SAMSUNG
Power	15W
Driver included	PHILIPS
Driver available	1-10V DALI
Lumen	1550 Lm
MacAdam	4SDC
Beam	87°
CCT	3000K
CRI	≥80
UGR	<19
LED Life	30.000 h
Insulation class	Class II
IP	44
Material	Aluminum
Warranty	5 years
Net Weight	0,630 Kg
Volume	0,0027 m³
Base / Hole	ø 12,5 cm



DOWNLIGHT

Die-cast aluminum recessed spotlight with round seal. Suitable for the installation on plasterboard ceiling. Matt white finish; COB Chip on Board and SMD technology; available in different color temperatures 3000k and 4000k and with three different optics; CRI ≥ 80; protection IP20; insulation class II.



IDEAL LUX s.r.l.

Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel. +39 041 5790500, Fax +39 041 8872349, E-mail info@ideal-lux.com
www.ideal-lux.com



Code	218830
Item name	BASIC DRIVER 1-10V 15W
Power	15W
Output	9/33Vdc
Current	450 mA
Measure	150 x 43 x 29 mm



Code	220796
Item name	BASIC DRIVER DALI 15W
Power	17W
Output	15/24Vdc
Current	700 mA
Measure	130 x 43 x 30 mm