

DOWNLIGHT

Modular system of aluminum recessed elements consisting of source, reflector and seal, with lenses and optional screens; white, chrome, black, gold finish; possible recess of round or square shape, symmetrical or symmetrical reflector; three different emission angles options. Light source with integrated LED COB technology for maximum efficiency, available with a color temperature of 2700 K, 3000 K or 4000 K; Energy efficient LED with high color rendering; CRI ≥90; starting binning ≤3- Step MacAdam; front protection IP54 (after installation of the product); insulation class II. Available in both DALI and 1-10V dimmable versions. Thanks to its compact size and great versatility, it is optimal for installation in DOMESTIC, MANAGERIAL and RETAIL indoor locations.



Code 208541

Item name DYNAMIC SOURCE 10W CRI90 2700K


Source LED COB CITIZEN

Power 10W

Driver included **DIMTRONIC** Driver available 1-10V | DALI Lumen 1500 Lm MacAdam 3SDC Beam 35° CCT 2700K CRI ≥90 UGR <25

LED Life 50.000 h
Insulation class Class II
IP 54

Material Aluminum
Warranty 5 years
Net Weight 0,150 Kg
Volume 0,0035 m³
Base / Hole Ø 6 cm







Code 216317

Item name DYNAMIC DRIVER 10W 1-10V

Power 10W Output 250 mA

Range _

Measure 135 x 20 x 30 mm



Code 216027

Item name DYNAMIC DRIVER DALI 17W

 Power
 17W

 Output
 250 mA

 Range
 200-700 mA

 Measure
 130 x 30 x 43 mm

Code 211763


Item name DYNAMIC LENS 20°



Code 211770

Item name DYNAMIC LENS 55°





Code 216317

Item name DYNAMIC FILTER HONEYCOMB

Code

208688

Item name

DYNAMIC FILTER ELLIPTICAL



Code 208640

Item name DYNAMIC LED BULB GU10 ADAPTER WHITE



Code 208657

Item name DYNAMIC LED BULB GU10 ADAPTER BLACK

