

ideal lux | Dynamic




DOWNLIGHT


Modular system of aluminum recessed elements consisting of source, reflector and seal, with lenses and optional screens; white, chrome, black, gold finish; possible recess of round or square shape, symmetrical or asymmetrical reflector; three different emission angles options. Light source with integrated LED COB technology for maximum efficiency, available with a color temperature of 2700 K, 3000 K or 4000 K; Energy efficient LED with high color rendering; CRI ≥ 90 ; starting binning ≤ 3 - Step MacAdam; front protection IP54 (after installation of the product); insulation class II. Available in both DALI and 1-10V dimmable versions. Thanks to its compact size and great versatility, it is optimal for installation in DOMESTIC, MANAGERIAL and RETAIL indoor locations.



Code	208596
Item name	DYNAMIC SOURCE 15W CRI90 4000K
Source	LED COB CITIZEN
Power	15W
Driver included	DIMTRONIC
Driver available	1-10V DALI
Lumen	1700 Lm
MacAdam	3SDC
Beam	35°
CCT	4000K
CRI	≥ 90
UGR	< 25
LED Life	50.000 h
Insulation class	Class II
IP	54
Material	Aluminum
Warranty	5 years
Net Weight	0,200 Kg
Volume	0,0035 m ³
Base / Hole	$\varnothing 6$ cm



6,5 cm



7,3 cm



Code	216324
Item name	DYNAMIC DRIVER 15W 1-10V
Power	15W
Output	250 mA
Range	.
Measure	101 x 29 x 51 mm



Code	216263
Item name	DYNAMIC DRIVER 15W DALI
Power	17W
Output	250 mA
Range	200-700 mA
Measure	130 x 30 x 43 mm


Code 211763
Item name DYNAMIC LENS 20°



Code 211770
Item name DYNAMIC LENS 55°



Code 216317
Item name DYNAMIC FILTER HONEYCOMB



Code 208688
Item name DYNAMIC FILTER ELLIPTICAL



Code 208640
Item name DYNAMIC LED BULB GU10 ADAPTER WHITE



Code 208657
Item name DYNAMIC LED BULB GU10 ADAPTER BLACK

