
ideal lux. Arca



Code	222967
Item name	ARCA TRACK 14W 36° 3000K
Source	LED SMD CREE
Power	14W
Driver included	No
Driver available	On/Off
Lumen	1400 Lm
MacAdam	3SDC
Beam	36°
CCT	3000K
CRI	≥80
UGR	<19
LED Life	50.000 h
Insulation class	Class III
IP	20
Material	Aluminum
Warranty	5 years
Net Weight	0,460 Kg
Volume	0,0030 m ³
Base / Hole	8,8 x 3,7 cm



LINEAR SYSTEM

Extruded aluminum linear system compatible with a wide range of lighting fittings with magnetic fixing and mechanical safety lock. The system is anodized and varnished. It is available in black color and for different kind of installations: ceiling, suspension, or flush in plasterboard ceilings. Modules can be assembledaccording to the desired arrangement. The body section for the ceiling and suspension versions is 42 mm wide and 85 mm high, while the body for recessed version is 86 mm wide and 90 mm high. Both models are available in two lengths: 1000 mm and 3000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with UGR control lower than 19, the TRACK or PENDANT modules for SPOT illumination with different emission angles. Integrated LEDs, possibility of color temperature of 3000 K or 4000 K; starting binning ≤3-Step MacAdam; min. 80% of luminous flux remaining after 50,000 h duration; IP20 protection; insulation class III. The 48V power supply gives great versatility and safety, with reversible settlement that can be modified if necessary. The system is suitable for environments where professional lighting with minimal design is required, such as OFFICES and SHOPS.







Suggestion

ideal lux. Arca

1. Code Item name Beam Measure

223094 ARCA LENS 18° FOR TRACK 14W 18° Ø 4,5 x 2,5 cm



ideal lux. Arca

DRIVER NOT INCLUDED | OPTIONAL



Code Item name Power Output Current Measure 223155 | 223162 | 223179 ARCA DRIVER ON/OFF 60W | 90W | 150W 48V 1300 mA | 2000 mA | 3200 mA 171x62x37 mm 220x68x37 mm 228x68x37 mm