
ideal lux. Arca



Code	222981
Item name	ARCA PENDANT 15W 34° 3000K
Source	LED COB
Power	15W
Driver included	CITIZEN
Driver available	No
Lumen	1450 Lm
MacAdam	SDCM 3
Beam	34°
CCT	3000K
CRI	≥80
UGR	<13
LED Life	50.000 h
Insulation class	Class III
IP	20
Material	Aluminum
Warranty	5 years
Net Weight	0,740 Kg
Volume	0,0056 m ³
Base / Hole	9 x 4 cm



LINEAR SYSTEM

Extruded aluminum linear system compatible with a wide range of lighting fittings with mechanical fixing. The system is anodized and varnished. It is available in black color and for different kind of installations: ceiling, suspension, or flush in plasterboard ceilings. odules can be assembled according to the desired arrangement. The body section for the ceiling and suspension versions is 42 mm wide and 85 mm high, while the body for recessed version is 86 mm wide and 90 mm high. Both models are available in two lengths: 1000 mm and 3000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with UGR control lower than 13, the TRACK or PENDANT modules for SPOT illumination with different emission angles. The CORNER module for angle composition. Integrated LEDs, possibility of color temperature of 3000 K or 4000 K; starting binning ≤3-Step MacAdam; IP20 protection; insulation class III. The 48Vdc power supply gives great versatility and safety, with reversible settlement that can be modified if necessary. The system is suitable for environments where professional lighting with inimal design is required, such as OFFICES and SHOPS.







ideal lux. Arca

Code Item name 223285 ARCA LENS 18° FOR PENDANT 14W

