

ideal lux | Dynamic




DOWNLIGHT


Modular system of aluminum recessed elements consisting of source, reflector and seal, with lenses and optional screens; white, chrome, black, gold finish; possible recess of round or square shape, symmetrical or asymmetrical reflector; three different emission angles options. Light source with integrated LED COB technology for maximum efficiency, available with a color temperature of 2700 K, 3000 K or 4000 K; Energy efficient LED with high color rendering; CRI ≥ 90 ; starting binning ≤ 3 - Step MacAdam; front protection IP54 (after installation of the product); insulation class II. Available in both DALI and 1-10V dimmable versions. Thanks to its compact size and great versatility, it is optimal for installation in DOMESTIC, MANAGERIAL and RETAIL indoor locations.



Code	252988
Item name	DYNAMIC SOURCE 09W CRI90 3000K
Source	LED COB CITIZEN
Power	9W
Driver included	DIMTRONIC
Driver available	1-10V DALI
Lumen	1000 Lm
MacAdam	3SDC
Beam	35°
CCT	3000K
CRI	≥ 90
UGR	<25
LED Life	50.000 h
Insulation class	Class II
IP	54
Material	Aluminum
Warranty	5 years
Net Weight	0,200 Kg
Volume	0,0035 m ³
Base / Hole	\varnothing 6 cm



5,6 cm



5,1 cm



Code	253008
Item name	DYNAMIC DRIVER 1-10V 12W
Power	12W
Output	200 mA
Range	120-350 mA
Measure	125 x 45 x 27 mm



Code	253015
Item name	DYNAMIC DRIVER DALI 12W
Power	11W
Output	200 mA
Current	100-400 mA
Measure	130 x 30 x 43 mm


Code 211763
Item name DYNAMIC LENS 20°



Code 211770
Item name DYNAMIC LENS 55°



Code 216317
Item name DYNAMIC FILTER HONEYCOMB



Code 208688
Item name DYNAMIC FILTER ELLIPTICAL



Code 208640
Item name DYNAMIC LED BULB GU10 ADAPTER WHITE



Code 208657
Item name DYNAMIC LED BULB GU10 ADAPTER BLACK

