

ideal lux | Game Round



DOWNLIGHT

Die-cast aluminum recessed spotlight with round or square seal, suitable for the installation on plasterboard ceilings. Matt chrome finish, matt white RAL 9001, matt black RAL 9011, matt gold RAL 1032. COB-Chip on Board technology for maximum efficiency; available with color temperatures 2700 K, 3000 K or 4000 K. Assembling and disassembling without utensils; protection IP20; insulation class II; LED useful life 30.000 h L70B50. It can be dimmed with 1-10V and DALI.



Suggestion




Suggestion



Suggestion

Code	267968
Item name	GAME ROUND 11W BK BK 4000K
Source	LED COB CREE
Power	11W
Driver included	ON-OFF
Driver available	1-10V DALI
Lumen	850 Lm
MacAdam	SDCM5
Beam	36°
CCT	4000K
CRI	≥85
UGR	<19
LED Life	30.000 h
Insulation class	Class II
IP	20
Material	Aluminum
Warranty	5 years
Net Weight	0,280 Kg
Volume	0,0011 m³
Base / Hole	ø 7,4 cm





Code	217253
Item name	GAME DRIVER 1-10V
Power	12W
Output	9/40Vdc
Current	250 mA
Measure	150 x 43 x 29 mm



Code	202396
Item name	GAME DRIVER DALI
Power	11W
Output	10/28Vdc
Current	250 mA
Measure	135 x 20 x 30 mm